



ELS-ST

Şerit Led




Ürün Modeli	Giriş Voltaj	PCB Eni(mm)	LED Sayısı (1mt)	Güç (W)	Işık Akısı (lm/m)	Verimlilik (lm/W)
ELS-ST80W8_12V	12V DC	8	80	10 W/m	1752	176
ELS-ST80W10_12V	12V DC	10	80	10 W/m	1752	176
ELS-ST160W8_12V	12V DC	8	160	10 W/m	1802	181
ELS-ST160W10_12V	12V DC	10	160	10 W/m	1802	181
ELS-ST80W8_24V	24V DC	8	80	10 W/m	1752	176
ELS-ST80W10_24V	24V DC	10	80	10 W/m	1752	176
ELS-ST160W8_24V	24V DC	8	160	10 W/m	1802	181
ELS-ST160W10_24V	24V DC	10	160	10 W/m	1802	181
ELS-ST140W5_24V	24V DC	5	140	10 W/m	1574	158




Seçenekler

Işık Rengi Seçenekleri



CRI (Renksel Geriverim) Seçenekleri



Kontrol Seçenekleri



Elco LED ST Serisi

İnce, Güçlü ve Uzun Ömürlü Işık Çizgisi

Elco LED'in ST Serisi, yüksek verimlilik ve uzun ömür beklentisini kompakt tasarımıyla buluşturur. 12V ve 24V seçenekleriyle her projede stabil ışık sağlar; 5 mm, 8 mm ve 10 mm genişlik alternatifleri ise dar detaylardan geniş hatlara kadar kusursuz uyum sunar. Premium LED yapısı, homojen ışık ve güvenilir performansıyla ST Serisi'ni mimari aydınlatmada ideal bir profesyonel çözüm haline getirir.



Elco LED ST Series


A Sleek, Robust, and Enduring Line of Light

Elco LED's ST Series combines high efficiency and longevity with a compact design. Offering 12V and 24V options, it ensures stable illumination for every project; while the 5mm, 8mm, and 10mm width alternatives provide a flawless fit from narrow details to broad lines. With its premium LED structure, homogeneous light output, and reliable performance, the ST Series stands out as the ideal professional solution for architectural lighting.

Elco Linear - ST Series Strip Lights




Product Model	Input	Width (mm)	LED Count (1m)	Power (W)	Intensity (lm/m)	Efficiency (lm/W)
ELS-ST80W8_12V	12V DC	8	80	10 W/m	1752	176
ELS-ST80W10_12V	12V DC	10	80	10 W/m	1752	176
ELS-ST160W8_12V	12V DC	8	160	10 W/m	1802	181
ELS-ST160W10_12V	12V DC	10	160	10 W/m	1802	181
ELS-ST80W8_24V	24V DC	8	80	10 W/m	1752	176
ELS-ST80W10_24V	24V DC	10	80	10 W/m	1752	176
ELS-ST160W8_24V	24V DC	8	160	10 W/m	1802	181
ELS-ST160W10_24V	24V DC	10	160	10 W/m	1802	181
ELS-ST140W5_24V	24V DC	5	140	10 W/m	1574	158




Options

Light Color Options



CRI Options



Control System Options



* The weight information does not include the driver.
* The given luminous flux values are based on 4000K. Diffuser cover material may vary by ±10%.
* Elco LED reserves the right to change the information on this page without prior notice.